



SPECIFICATIONS:

PART NUMBER:

HG2TAHSP-XX-XX

(Ex: Single Color Blue/Red: HG2TAHSP-BR-XX)

(Ex: Dual Color Blue/Red With
White Flood: HG2TAHSP-BR-WW)

APPLICATION:

Exterior Use

MOUNTING:

Surface mount (no drilling required)

DIMENSIONS:

Length: 61.100"

Height: 1"

Depth: 5"

INPUT VOLTAGE:

9 - 15 VDC

STAND-BY CURRENT DRAW:

.001A

OPERATING TEMPERATURE:

-4° to 185° F (-20° to 85° C)

CURRENT DRAW:

1.5A Average

1A min. / 3A max. dependent on flash pattern

1A min. / 3A max. dependent on flash pattern

60 5mm High-intensity, wide-angle LEDs

FLASH PATTERNS:

20

CHASSIS:

Black Finish Powder Coated Aluminum Housing

CERTIFICATIONS:

SAE J595 Class 1, Title 13

WARRANTY:

5 Year Warranty

PROUDLY DESIGNED AND MADE IN THE USA.

BLACK (-) Chassis Ground

RED (+) 12V Constant Power

WHITE (+) Switched Power



* Please see full wiring diagram
for addition information

