



SPECIFICATIONS:

PART NUMBER:
HG2ZD1M-XX-XX
(Ex: Single Color Blue/Red: HG2ZD1M-BR-XX)
(Ex: Dual Color Blue/Red With White Flood: HG2ZD1M-BR-WW)

APPLICATION:
Exterior and Interior Use

MOUNTING:
Vehicle Specific Bracket or Universal Surface Mount

DIMENSIONS:
Length: 10.44"
Height: 0.572"
Depth: 1.461"

INPUT VOLTAGE:
9 - 15 VDC

STAND-BY CURRENT DRAW:
.001A

OPERATING TEMPERATURE:
-4° to 185° F (-20° to 85° C)

CURRENT DRAW:
1.5A Average
1A min. / 3A max. dependent on flash pattern
1A min. / 3A max. dependent on flash pattern
60 5mm High-intensity, wide-angle LEDs

FLASH PATTERNS:
20

CHASSIS:
Black Finish Powder Coated Aluminum Housing

CERTIFICATIONS:
SAE J595 Class 1, Title 13

WARRANTY:
5 Year Warranty

PROUDLY DESIGNED AND MADE IN THE USA.

- BLACK** (-) Chassis Ground
- RED** (+) 12V Constant Power
- WHITE** (+) Switched Power
- BROWN** (+) Takedown Power
- GREEN** (+) Cruise Mode
- BLUE** (+) Momentary Pattern
- YELLOW** (+) Right Directional
- ORANGE** (+) Left Directional

* Please see full wiring diagram for addition information

