



**SPECIFICATIONS:**

**PART NUMBER:**  
HG2ZD4M-XX-XX  
(Ex: Single Color Blue/Red: HG2ZD4M-BR-XX)  
(Ex: Dual Color Blue/Red With White Flood: HG2ZD4M-BR-WW)

**APPLICATION:**  
Exterior and Interior Use

**MOUNTING:**  
Vehicle Specific Bracket or Universal Surface Mount

**DIMENSIONS:**  
Length: 44.97"  
Height: 0.572"  
Depth: 1.461"

**INPUT VOLTAGE:**  
9 - 15 VDC

**STAND-BY CURRENT DRAW:**  
.001A

**OPERATING TEMPERATURE:**  
-4° to 185° F (-20° to 85° C)

**CURRENT DRAW:**  
1.5A Average

1A min. / 3A max. dependent on flash pattern  
1A min. / 3A max. dependent on flash pattern  
60 5mm High-intensity, wide-angle LEDs

**FLASH PATTERNS:**  
20

**CHASSIS:**  
Black Finish Powder Coated Aluminum Housing

**CERTIFICATIONS:**  
SAE J595 Class 1, Title 13

**WARRANTY:**  
5 Year Warranty

**PROUDLY DESIGNED AND MADE IN THE USA.**

- BLACK** (-) Chassis Ground
- RED** (+) 12V Constant Power
- WHITE** (+) Switched Power
- BROWN** (+) Takedown Power
- GREEN** (+) Cruise Mode
- BLUE** (+) Momentary Pattern
- YELLOW** (+) Right Directional
- ORANGE** (+) Left Directional

\* Please see full wiring diagram for addition information

