

HG2 QUARTER WINDOW

Chevy Tahoe Configuration



To Select Master

Connect WHITE (Pattern_Sel) to RED. BLACK to Ground. Apply 12V to RED and WHITE for 5 seconds. Module will light up 6 LEDs of top row.

To Select Slave P2

Connect WHITE (Pattern_Sel) to RED. BLACK to Ground. Apply 12V to RED and WHITE for 5 seconds. Module will Light up 3 LEDs on the right side of DS1.

Change Patterns

Apply 12V to WHITE (Pattern_Sel) for less than 5 seconds.

Wires

Black (G) - Ground
White (P) - Pattern Select
Yellow (S) - SYNC
Red (V) - Power
Blue (T) - Takedown

Configurations

There are three configuration for the same board

- 1) Master Phase 1
- 2) Slave Phase 1
- 3) Slave Phase 2

All boards start out as Slave. When running, if Blue (Takedown) is high (12V), Slave is Phase 2. If Blue is unconnected or low, Slave is Phase 1.

To Select Slave P1

Connect WHITE (Pattern_Sel) to RED. BLACK to Ground. Apply 12V to RED and WHITE for 5 seconds. Module will light up 3 LEDs on the left side of DS1.

Change Back to First Pattern

After already being powered up, apply 12V to WHITE (Pattern_Sel) for more than 5 seconds.

Takedown

Apply 12V to BLUE (Takedown). This overrides current pattern.